

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR

PREFERRED EMBODIMENT TO LED LIGHT STRING

Inventor: Mark R. Allen

Prepared by: Weiser & Associates, P.C.  
230 S. 15<sup>th</sup> Street, Suite 500  
Philadelphia, Pennsylvania 19102  
(215) 875-8383

\* \* \* \* \*

Certification Under 37 CFR 1.10

"Express Mail" Mailing Label No. EL 1785044605 Date of Deposit 6/24/99

I hereby certify that this document is being deposited with the United States Postal Service's "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

THERESE McKINLEY  
(Name of person mailing)

Therese McKinley  
(Signature of person mailing)

## Preferred Embodiment to Led Light String

## CROSS REFERENCES TO RELATED APPLICATIONS

This application is a continuation-in-part of copending application serial number 09/141,914 filed August 28, 1998, titled LED LIGHT STRING EMPLOYING SERIES-PARALLEL BLOCK  
 5 COUPLING and bearing Attorney Docket No. 1009.002, the entire disclosure of which copending application is incorporated herein by reference. This application claims benefit of U.S. Provisional Application No. 60/119,804, filed February 12, 1999.

## BACKGROUND OF THE INVENTION

Field of Invention

10 The present invention relates to light strings and, more particularly, to decorative light strings employing LEDs.

Description of Related Art

15 Light emitting diodes (LEDs) are increasingly employed as a basic lighting source in a variety of forms, including decorative lighting, for reasons among the following. First, as a device, LEDs have a very long lifespan, compared with common incandescent and fluorescent sources, with typical LED lifespan at least 100,000 hours. Second, LEDs have several favorable physical properties, including ruggedness, cool operation, and ability to operate under wide temperature variations. Third, LEDs are currently available in all primary and several secondary colors, as well as in a "white" form employing a blue source and phosphors. Fourth, with newer doping techniques, LEDs are becoming increasingly  
 20 efficient, and colored LED sources currently available may consume an order of magnitude less power than incandescent bulbs of equivalent light output. Finally, with expanding applications and resulting larger volume demand, as well as with new manufacturing techniques, LEDs are increasingly cost effective.

25 LED-based light strings, used primarily for decorative purposes such as for Christmas lighting, is one application for LEDs. For example, U.S. patent 5,495,147 entitled LED LIGHT STRING

SYSTEM to Lanzisera (hereinafter "Lanzisera") and U.S. patent 4,984,999 entitled STRING OF LIGHTS SPECIFICATION to Leake (hereinafter "Leake") describe different forms of LED-based light strings. In both Lanzisera and Leake, exemplary light strings are described employing purely parallel wiring of discrete LED lamps using a step-down transformer and rectifier power conversion scheme.

5 These and all other LED light string descriptions found in the prior art convert input electrical power, usually assumed to be the common U.S. household power of 110 VAC to a low voltage, nearly DC input. The present invention relaxes this input electrical power conversion and specifies a preferred embodiment in which the LED light string is electrically powered directly from either a common household 110 VAC or 220 VAC source, without a lower voltage involved via power conversion. The

10 LEDs may be driven using household AC, rather than DC, because the nominal LED forward bias voltage, if used in reverse bias fashion, is generally much lower than the reverse voltage where the LED p-n junction breaks down. When LEDs are driven by AC, pulsed light is effected at the AC rate (e.g., 60 or 50 Hz), which is sufficiently high in frequency for the human eye to integrate and see as a continuous light stream.

## 15 SUMMARY OF THE INVENTION

The present invention relates to a light string, including a pair of wires connecting to a standard household AC electrical plug; a plurality of LEDs powered by the pair of wires, wherein the LEDs are electrically coupled in series to form at least one series block; multiple series blocks, if employed, that are electrically coupled in parallel; a standard household AC socket at the opposite end for connection

20 of multiple light strings in an end-to-end, electrically parallel fashion.

## BRIEF DESCRIPTION OF THE DRAWINGS

Other aspects, features and advantages of the present invention will become more fully apparent from the following detailed description, the appended claims, and the accompanying drawings in which:

FIG. 1 shows two example block diagrams of the light string in its embodiment preferred primarily, with one diagram for a 110 VAC common household input electrical source (e.g., 60 Hz) and one diagram for a 220 VAC common household (e.g., 50 Hz) input electrical source.

25

FIG. 2 shows two example schematic diagrams of the light string corresponding to the two block diagrams in FIG. 1 for either the 110 VAC or the 220 VAC input electrical source.

FIG. 3 shows two example block diagrams of the light string in its embodiment preferred alternatively, with one diagram for a 110 VAC common household input electrical source (e.g., 60 Hz) and one diagram for a 220 VAC common household (e.g., 50 Hz) input electrical source.

FIG. 4 shows an example schematic diagram of the AC-to-DC power supply corresponding to the two block diagrams in FIG. 3 for either the 110 VAC or the 220 VAC input electrical source.

FIG. 5 shows an example pictorial diagram of the manufactured light string in either its "straight" or "curtain" form (either form may be manufactured for 110 VAC or 220 VAC input).

FIG. 6 shows an example pictorial diagram of special tooling of the housing for an LED housing in the light string, for assurance of proper LED electrical polarity throughout the light string circuit.

FIG. 7 shows an example pictorial diagram of special tooling and manufacturing of the LED and its housing in the light string, for assurance of proper LED polarity using the example in FIG. 6.

FIG. 8 shows an example pictorial diagram of a fiber optic "icicle" attached to an LED and its housing in the light string, where the "icicle" diffuses the LED light in a predetermined manner.

### DETAILED DESCRIPTION

The term "alternating current voltage", sometimes abbreviated as "VAC", as used herein occasionally refers to a numerical amount of volts, for example, "220 VAC". It is to be understood that the stated number of alternating current volts is the nominal voltage which cycles continuously in forward and reverse bias and that the actual instantaneous voltage at a given point in time can differ from the nominal voltage number.

In accordance with the present invention, an LED light string employs a plurality of LEDs wired in series-parallel form, containing at least one series block of multiple LEDs. The series block size is

determined by the ratio of the standard input voltage (e.g., either 110 VAC or 220 VAC) to the drive voltage(s) of the LEDs to be employed (e.g., 2 VDC). Further, multiple series blocks, if employed, are each of the same LED configuration (same number and kinds of LEDs), and are wired together along the string in parallel. LEDs of the light string may comprise either a single color LED or an LED including multiple sub-dies each of a different color. The LED lenses may be of any shape, and may be either clear, clear-colored, or diffuse-colored. Moreover, each LED may have internal circuitry to provide for intermittent on-off blinking and/or intermittent LED sub-die color changes. Individual LEDs of the light string may be arranged continuously (using the same color), or periodically (using multiple, alternating colors), or pseudo-randomly (any order of multiple colors). The LED light string may provide an electrical interface to couple multiple lights strings together in parallel, and physically from end to end. Fiber optic bundles or strands may also be coupled to individual LEDs to diffuse LED light output in a predetermined manner.

An LED light string of the present invention may have the following advantages. The LED light string may last far longer and require less power consumption than light strings of incandescent lamps, and they may be safer to operate since less heat is generated. The LED light string may have reduced cost of manufacture by employing series-parallel blocks to allow operation directly from a standard household 110 VAC or 220 VAC source, either without any additional circuitry (AC drive), or with only minimal circuitry (DC drive). In addition, the LED light string may allow multiple strings to be conveniently connected together, using standard 110 VAC or 220 VAC plugs and sockets, desirably from end-to-end.

Direct AC drive of LED light string avoids any power conversion circuitry and additional wires; both of these items add cost to the light string. The additional wires impose additional mechanical constraint and they may also detract aesthetically from the decorative string. However, direct AC drive results in pulsed lighting. Although this pulsed lighting cannot be seen at typical AC drive frequencies (e.g. 50 or 60 Hz), the pulsing itself is not the most efficient use of each LED device because less overall light is produced than if the LEDs were continuously driven using DC. This lower amount of light produced may be compensated for by using more expensive, brighter LEDs, and thus an engineering tradeoff exists, where AC drive is of primary preference, and DC drive is preferred alternatively.

FIG. 1 shows the embodiment of an LED light string in accordance with the present invention, and as preferred primarily through AC drive. In FIG. 1, the two block diagrams correspond to a exemplary string employing 100 LEDs, for either 110 VAC (top diagram) or 220 VAC (bottom diagram) standard household current input (e.g., 50 or 60 Hz). In the top block diagram of FIG. 1, the input electrical interface consists merely of a standard 110 VAC household plug **101** attached to a pair of drive wires. With the average LED drive voltage assumed to be approximately 2.2 V in FIG. 1, the basic series block size for the top block diagram, corresponding to 110 VAC input, is approximately 50 LEDs. Thus, for the 110 VAC version, two series blocks of 50 LEDs **102** are coupled in parallel to the drive wires along the light string. The two drive wires for the 110 VAC light string terminate in a standard 110 VAC household socket **103** to enable multiple strings to be connected in parallel electrically from end-to-end.

In the bottom block diagram of FIG. 1, the input electrical interface likewise consists of a standard 220 VAC household plug **104** attached to a pair of drive wires. With again the average LED drive voltage assumed to be approximately 2.2 V in FIG. 1, the basic series block size for the bottom diagram, corresponding to 220 VAC input, is 100 LEDs. Thus, for the 220 VAC version, only one series block of 100 LEDs **105** is coupled to the drive wires along the light string. The two drive wires for the 220 VAC light string terminate in a standard 220 VAC household socket **106** to enable multiple strings to be connected in parallel from end-to-end. Note that for either the 110 VAC or the 220 VAC light string, the standard plug and socket employed in the string varies in accordance to the country in which the light string is intended to be used.

As an alternative preference to AC drive, FIG. 3 shows two block diagrams that correspond to a exemplary string employing 100 LEDs and DC drive, for either 110 VAC (top diagram) or 220 VAC (bottom diagram) standard household current input (e.g., 50 or 60 Hz). In the top block diagram of FIG. 3, the input electrical interface consists of a standard 110 VAC household plug **301** attached to a pair of drive wires, followed by an AC-to-DC converter circuit **302**. As in FIG. 1, with the average LED drive voltage assumed to be approximately 2.2 V in FIG. 3, the basic series block size for the top block diagram, corresponding to 110 VAC input, is approximately 50 LEDs. Thus, for the 110 VAC version, two series blocks of 50 LEDs **303** are coupled in parallel to the output of the AC-to-DC converter **302** using additional feed wires along the light string. The two drive wires for the 110 VAC light string

terminate in a standard 110 VAC household socket **304** to enable multiple strings to be connected in parallel electrically from end-to-end.

In the bottom block diagram of FIG. 3, the input electrical interface likewise consists of a standard 220 VAC household plug **305** attached to a pair of drive wires, followed by an AC-to-DC converter circuit **306**. With again the average LED drive voltage assumed to be approximately 2.2 V in FIG. 3, the basic series block size for the bottom diagram, corresponding to 220 VAC input, is 100 LEDs. Thus, for the 220 VAC version, only one series block of 100 LEDs **307** is coupled to the output of the AC-to-DC converter **307** using additional feed wires along the light string. The two drive wires for the 220 VAC light string terminate in a standard 220 VAC household socket **308** to enable multiple strings to be connected in parallel from end-to-end. Note that for either the 110 VAC or the 220 VAC light string, the standard plug and socket employed in the string varies in accordance to the country in which the light string is intended to be used.

FIG. 4 shows an example schematic electrical diagram for the AC-to-DC converter employed in both diagrams of FIG. 3. The AC input to the circuit in FIG. 1 is indicated by the symbol for an AC source **401**. A varistor **402** may optionally be used to ensure that voltage is limited during power surges. The actual AC to DC rectification is performed by use of a full-wave bridge rectifier **403**. This bridge rectifier **403** results in a rippled DC current and therefore serves as an example circuit only. A different rectification scheme may be employed, depending on cost considerations. For example, one or more capacitors or inductors may be added to reduce ripple at only minor cost increase. Because of the many possibilities, and because of their insignificance, these and similar additional circuit features have been purposely omitted from FIG. 4.

For either the 110 VAC or the 220 VAC version of the LED light string, and whether or not an AC-to-DC power converter is used, the final manufacturing may be a variation of either the basic "straight" string form or the basic "curtain" string form, as shown in the top and bottom pictorial diagrams in FIG. 5. In the basic "straight" form of the light string, the standard (110 VAC or 220 VAC) plug **501** is attached to the drive wires which provide power to the LEDs **502** via the series-parallel feeding described previously. The two drive and other feed wires **503** are twisted together along the length of the light string for compactness and the LEDs **502** in the "straight" form are aligned with these twisted wires **503**, with the LEDs **502** spaced uniformly along the string length (note drawing is not to

scale). The two drive wires in the "straight" form of the light string terminate in the standard (correspondingly, 110 VAC or 220 VAC) socket **504**. Typically, the LEDs are spaced uniformly every four inches.

In the basic "curtain" form of the light string, as shown pictorially in the bottom diagram of FIG. 5, the standard (110 VAC or 220 VAC) plug **501** again is attached to the drive wires which provide power to the LEDs **502** via the series-parallel feeding described previously. The two drive and other feed wires **503** are again twisted together along the length of the light string for compactness. However, the feed wires to the LEDs are now twisted and arranged such that the LEDs are offset from the light string axis in small groups (groups of 3 to 5 are shown as an example). The length of these groups of offset LEDs may remain the same along the string or they may vary in either a periodic or pseudo-random fashion. Within each group of offset LEDs, the LEDs **502** may be spaced uniformly as shown or they may be spaced nonuniformly, in either a periodic or pseudo-random fashion (note drawing is not to scale). The two drive wires in the "curtain" form of the light string also terminate in a standard (correspondingly 110 VAC or 220 VAC) socket **504**. Typically, the LED offset groups are spaced uniformly every six inches along the string axis and, within each group, the LEDs are spaced uniformly every four inches.

In any above version of the preferred embodiment to the LED light string, blinking may be obtained using a number of techniques requiring additional circuitry, or by simply replacing one of the LEDs in each series block with a blinking LED. Blinking LEDs are already available on the market at comparable prices with their continuous counterparts, and thus the light string may be sold with the necessary (e.g., one or two) additional blinkers included in the few extra LEDs.

In wiring any version of the preferred embodiment to the light string, as described previously, it is critical that each LED is powered using the correct LED polarity. This equates to all feeds coming from the same drive wire always entering either the positive or the negative lead of each LED. Since the drive wires are AC, it does not matter whether positive or negative is chosen initially – it is only important all the LEDs in each series block have the same polarity orientation (either all positive first or all negative first). In order to facilitate ease of proper manufacturing, as well as ease of proper LED bulb replacement by the user, each LED and its assembly into its housing may be modified to insure proper polarity. An example modification is shown in FIG. 6, where the LED (shown at far left with



A a rectangular, arched-top lens) is modified to include a keyed offset on its <sup>601</sup>base ~~601~~<sup>holder 606</sup>, and accordingly,  
 A the LED lamp base <sup>605</sup>incorporates a notch **602** to accommodate this keyed offset. This first pair of  
 5 A modifications, useful for manufacturing only, results in the LED being properly mounted within its base  
 A holder on the light string, the lamp base is also modified to include a keyed offset <sup>603</sup>on its base ~~603~~<sup>605</sup>, and  
 the lamp <sup>assembly 607</sup>holder is correspondingly notched **604** for proper alignment. This second pair of modifications  
 is useful in both manufacturing and by the user, for properly placing or replacing the LED lamp bulb  
 into its holder on the light string. The LED lamp base and holder collectively form the LED housing.

In manufacturing the above modification to assure proper LED polarity, it may be advantageous  
 10 to build the LED mold such that two piece replaceable LED lamp bulb described in FIG. 6 can be made  
 in one step as a single piece. This is illustrated in FIG. 7, where the single piece replaceable LED lamp  
 bulb **701** has a single keyed offset to fit into its notched lamp holder **702**. Although this requires more  
 elaborate modification of the LED base, the resulting assembly is now composed of two, rather than  
 three, LED pieces and as such, may allow the lights string to be made more rapidly and at lower cost.

15 Typically, the LEDs in the light string will incorporate a lens for wide-angle viewing. However,  
 it is also possible to attach fiber optic bundles or strands to the LEDs to spatially diffuse the LED light  
 in a predetermined way for a visual effect. In such case, the LED lens is designed to create a narrow-  
 angle light beam (e.g., 20 degree beamwidth) along its axis, to enable the LED light to flow through the  
 fiber optics with high coupling efficiency. An example of the use of fiber optics is shown in FIG. 8,  
 20 where a very lossy fiber optic rod is employed with intention for the fiber optic rod to glow like an  
 illuminated "icicle." In FIG. 8, the LED **801** and its housing **802** may be attached to the fiber optic rod  
**803** using a short piece of tubing **804** that fits over both the LED lens and the end of the fiber optic rod  
 (note that the drawing is not to scale). An example design uses a cylindrical LED lens with a narrow-  
 angle end beam, where the diameter of the LED lens and the diameter of the fiber optic rod are the same  
 25 (e.g., 5 mm or 3/16 inches). The fiber optic rod **803** is typically between three to eight inches in length  
 and may be either uniform in length throughout the light string, or the fiber optic rod length may vary  
 in either a periodic or pseudo-random fashion.

Although the fiber optic rod **803** in FIG. 8 may be constructed using a variety of plastic or glass  
 materials, it is preferred that the rod be made in either a rigid form using clear Acrylic plastic or clear

crystal styrene plastic, or in a highly flexible form using Polyvinyl Chloride (PVC) plastic. These plastics are preferred for safety, durability, light transmittance, and cost reasons. It may be desirable to add into the plastic rod material either air bubbles or other constituents, such as tiny metallic reflectors, to achieve the designed measure of lossiness for off-axis glowing (loss) versus on-axis light conductance. Moreover, if PVC or crystal styrene are to be used, it may be desirable to add UV inhibiting chemicals such as a combination of hindered amine light stabilizer (HALS) chemicals. The tubing **804** that connects the fiber optic rod **803** to its LED lens **801** may also be made from a variety of materials, and be specified in a variety of ways according to opacity, inner diameter, wall thickness, and flexibility. From safety, durability, light transmittance, and cost reasons, it is preferred that the connection tubing **804** be a short piece (e.g., 10 mm in length) of standard clear flexible PVC tubing (containing UV inhibiting chemicals) whose diameter is such that the tubing fits snugly over both the LED lens and the fiber optic rod (e.g., standard wall tubing with 1/4 inch outer diameter). An adhesive may be used to hold this assembly more securely.

It will be understood that various changes in the details, materials and arrangements of the parts which have been described and illustrated in order to explain the nature of this invention may be made by those skilled in the art without departing from the principle and scope of the invention as expressed in the following claims.